




LOGGIA
industria vernici

TECHNICAL DATA SHEET

Revisione: 12 settembre 2019



Stucco in pasta per esterno

Basecoat putty for exterior use

General Characteristics

- Product:** Specific paste putty for grouting cracks on external walls. Based on acrylic resins and inerts quartz it is elastic, with good filling power and has a minimal shrinkage.
- Use:** Excellent filling and sandability power with fast drying and low shrinkage. Suitable for the correction of craters and lesions on the substrates to be painted. Excellent for external walls smoothing.

Application

Preparation of the surface: The surface must be healthy, free from grease or wax. Eliminate non-adherent or peeling parts. In case of chalking support, apply a coat of ISOL 45. In case of cracks open them by means of a specific electric tool and carefully remove all traces of dirt or dust.



Product Application

Methods:



Trowel, Spatula and American Spatula: Apply the product as it is. Proceed with subsequent smoothing with a steel trowel or spatulas to fill cracks and depressions.



Temperature of application:	+5 ÷ +35	°C
Relative humidity of application:	< 85%	
Recommended thickness:	0,5 ÷ 1	mm
Sanding after:	1	h
Complete curing:	6	h
Cleaning tools:	with water	

Technical characteristics

density:	1,75 ÷ 1,85	Kg/l
Viscosity:		
pH:	7 - 8	
Weight Solids::	80%	
Theoretical yield	0,8 – 1	mq/Kg
Colour:	white	
Feature:	mat	
Pack size:	20	Kg

Storage



Shelf-life: 2 years in original tightly closed containers away from direct sunlight and excessive heat.

The can should be resealed and stored tightly closed to prevent evaporation of the product and entry of air. Store it upside down after use.



Min storage temperature: +5°C (41°F)

Max storage temperature: +30°C (86°F)

Safety Precautions

Refer to the Material Safety Data Sheet before use

General Information

Every care is taken to ensure that the information provided in this technical data sheet is accurate. **Loggia Industria Vernici S.r.l.** takes no responsibility for the results obtained through the use of this product in as much as it is not possible for **Loggia Industria Vernici S.r.l.** to check or control the application method used. For this reason, we recommend that you check carefully that each product chosen, is suitable for each individual use to which it is put.

Loggia Industria Vernici S.r.l. Via Colle d'Alba di Levante – 04016 B.go S. Donato - Sabaudia (LT) – ITALY

Tel. (+39) 0773 562212, Fax (+39) 0773 562034. www.loggia.it, E-mail commerciale@loggia.it.

Company with Certified Quality System by BVQI according to UNI EN ISO 9001:2000.